

specifications?

E. Is the sediment control system or the pond system well

maintained and in good working condition?

Significant Rainfall Event Planning Checklist

Completed by ESC Supervisor – Copy Must Remain On-Site

Site Add	ress:			
Site Supe	erintendent Name:			
ESC Supe	ervisor Name:			
Develope	eloper/Duly Authorized Agent Name: Phone:			
Date:	File #	_		
•	ired that the ESC Supervisor completes the following checkli 5mm over 24hr period). ITEM AND/OR LOCATION TO CHECK	st 48 hours before a for CONDITIONS	recasted significa	nt rainfall COMPLETED
A. Aı	re the sediment fences adequate and/or erected correctly?			
•	Geotextile sediment fence buried at least 200mm below ground and properly compacted			
•	Sediment fencing installed parallel to slope contours and posts installed at minimum 2m spacing			
•	Built up sediment does not exceed 1/3 of the height of the sediment fence			
•	No tears or rips in existing silt fence fabric			
•	Not covered over by materials			
B. Do	pes the wheel wash or the entry/exit point (truck			
	and/pad) require maintenance?			
•	Does the wheel wash contain excessive sediment in its holding tank?			
•	Does the entry/exit pad exhibit excessive sediment accumulation and/or tracking offsite?			
•	Aggregate 100 to 150mm or greater			
C. Is	the road clean of sand, silt and mud?			
•	Do the trades staffs have the capacity to clean-up the sediment before they leave the site?			
•	Have you ensured sediment does not reach CB?			
D Ar	e the silt sack traps in place as per the FSC plan			

F.	Are Real-Time Monitoring Facilities connected and maintained?			
	 When was the system last calibrated? 			
G.	Are the 'wet trades' setting/washing up behind a sediment			
	fence and on grassed areas that will hold the volume of			
	waste?			
H.	Are roadside gutter check-dams installed upstream from the			
	CB inlets to preclude runoff diversion past CB inlets and			
	mitigate downstream flooding concerns?			
I.	Are the stockpiles/sand/soil adequately protected?			
	 Covered by a 6mil polyethylene sheets or tarps 			
	 Located behind a sediment fence 			
	2.11			
	 Sand bags around base of all temporary stockpiles, 			
	placed on paved or compacted surfaces to divert surface			
	runoff away from erodible materials			
J.	Do the temporary stockpiles on hard surfaces have:			
	Stockpile fully covered?			
	Perimeter control measures (i.e. sandbags, fibre or			
	geotextile) on the down slope of the stockpile?			
	• An up-slope diversion of sandbags, fibre or geofabric for			
	on-site stockpiles?			
K.	Are the grass/turf strips on the footpath cleared of			
	sediment, sand and mud?			
K.	Are the service trenches backfilled?			
L.	Are exposed surfaces of the trench protected with perimeter			
	control measures and/ or disturbed surface protection (i.e.			
	tarps or rock mulch)			
M	Are the temporary drainpipes correctly connected?			
741.	Are the temporary drampipes correctly connected.			
N.	Has the Developer been advised about erosion and sediment			
	control corrections?			
0.	Incidental Water Management			
	6			
P.	Polymer/Flocculent Additives			
0.	pH Mitigation			
	· · · · · · · · · · · · · · · · · · ·			
· · · · · · · · · · · · · · · · · · ·				
Notes:				